

WATTYL ESTAPOL INTERIOR POLYURETHANE GLOSS RANGE

Chemwatch Independent Material Safety Data Sheet

Issue Date: 3-Dec-2012

9317SP(cs)

CHEMWATCH 4796-75

Version No:1.1.1.1

CD 2012/4 Page 1 of 8

Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME

WATTYL ESTAPOL INTERIOR POLYURETHANE GLOSS RANGE

SYNONYMS

"Product Code: 1112 line: Gloss, Satin, Matt"

PROPER SHIPPING NAME

PAINT or PAINT RELATED MATERIAL

PRODUCT USE

■ Used according to manufacturer's directions.

The use of a quantity of material in an unventilated or confined space may result in increased exposure and an irritating atmosphere developing. Before starting consider control of exposure by mechanical ventilation.

SUPPLIER

Company: Valspar Paint (Australia) Pty Limited

Address:

Level 4/2 Burbank Place

Baulkham Hills

NSW, 2153

Australia

Telephone: +61 2 8867 3333

Emergency Tel: **1800 039 008**

Fax: +61 2 8867 3344

Section 2 - HAZARDS IDENTIFICATION

STATEMENT OF HAZARDOUS NATURE

HAZARDOUS SUBSTANCE. DANGEROUS GOODS. According to the Criteria of NOHSC, and the ADG Code.

RISK

Risk Codes

R10

R36/37/38

R43

R48/20

R52/53

R63(3)

R65

R66

R67

Risk Phrases

• Flammable.

• Irritating to eyes, respiratory system and skin.

• May cause SENSITISATION by skin contact.

• Harmful: danger of serious damage to health by prolonged exposure through inhalation.

• Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

• Possible risk of harm to the unborn child.

• HARMFUL- May cause lung damage if swallowed.

• Repeated exposure may cause skin dryness and cracking.

• Vapours may cause drowsiness and dizziness.

SAFETY

Safety Codes

S23

S24

S25

S36

S37

S39

S51

S09

S53

S401

S07

S13

S26

S46

Safety Phrases

• Do not breathe gas/fumes/vapour/spray.

• Avoid contact with skin.

• Avoid contact with eyes.

• Wear suitable protective clothing.

• Wear suitable gloves.

• Wear eye/face protection.

• Use only in well ventilated areas.

• Keep container in a well ventilated place.

• Avoid exposure - obtain special instructions before use.

• To clean the floor and all objects contaminated by this material, use water and detergent.

• Keep container tightly closed.

• Keep away from food, drink and animal feeding stuffs.

• In case of contact with eyes, rinse with plenty of water and contact Doctor or Poisons Information Centre.

• If swallowed, IMMEDIATELY contact Doctor or Poisons Information Centre. (show this container or label).

continued...

WATTYL ESTAPOL INTERIOR POLYURETHANE GLOSS RANGE

Chemwatch Independent Material Safety Data Sheet

Issue Date: 3-Dec-2012

9317SP(cs)

CHEMWATCH 4796-75

Version No:1.1.1.1

CD 2012/4 Page 2 of 8

Section 2 - HAZARDS IDENTIFICATION

S60 • This material and its container must be disposed of as hazardous waste.

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS RN	%
mineral turpentine	Not avail.	10-30
TDI / pentaerythritol monoricinoleate copolymer	52390-75-7	30-60
matting agent		NotSpec
contains <0.1% benzene		
No other ingredient information disclosed.		

Section 4 - FIRST AID MEASURES

SWALLOWED

- - If swallowed do NOT induce vomiting.
- If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.
- Observe the patient carefully.
- Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.
- Avoid giving milk or oils.
- Avoid giving alcohol.

EYE

- If this product comes in contact with the eyes:
- Wash out immediately with fresh running water.
- Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
- Seek medical attention without delay; if pain persists or recurs seek medical attention.
- Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

SKIN

- If skin contact occurs:
- Immediately remove all contaminated clothing, including footwear.
- Flush skin and hair with running water (and soap if available).
- Seek medical attention in event of irritation.

INHALED

- - If fumes or combustion products are inhaled remove from contaminated area.
- Lay patient down. Keep warm and rested.
- Prosthesis such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.
- Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.

NOTES TO PHYSICIAN

- Treat symptomatically.
- Any material aspirated during vomiting may produce lung injury. Therefore emesis should not be induced mechanically or pharmacologically.

For acute or short term repeated exposures to petroleum distillates or related hydrocarbons:

- Primary threat to life, from pure petroleum distillate ingestion and/or inhalation, is respiratory failure.
- Patients should be quickly evaluated for signs of respiratory distress (e.g. cyanosis, tachypnoea, intercostal retraction, obtundation) and given oxygen. Patients with inadequate tidal volumes or poor arterial blood gases (pO₂ 50 mm Hg) should be intubated.
- Arrhythmias complicate some hydrocarbon ingestion and/or inhalation and electrocardiographic evidence of myocardial injury has been reported; intravenous lines and cardiac monitors should be established in obviously symptomatic patients. The lungs excrete inhaled solvents, so that hyperventilation improves clearance.
- A chest x-ray should be taken immediately after stabilisation of breathing and circulation to document aspiration and detect the presence of pneumothorax.

continued...

Section 5 - FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

- - Water spray or fog.
- Alcohol stable foam.
- Dry chemical powder.
- Carbon dioxide.

FIRE FIGHTING

- - Alert Fire Brigade and tell them location and nature of hazard.
- May be violently or explosively reactive.
- Wear breathing apparatus plus protective gloves.
- Prevent, by any means available, spillage from entering drains or water course.

FIRE/EXPLOSION HAZARD

- - Liquid and vapour are flammable.
- Moderate fire hazard when exposed to heat or flame.
- Vapour forms an explosive mixture with air.
- Moderate explosion hazard when exposed to heat or flame.

Combustion products include: carbon dioxide (CO₂), nitrogen oxides (NO_x), other pyrolysis products typical of burning organic material.

Contains low boiling substance: Closed containers may rupture due to pressure buildup under fire conditions.

FIRE INCOMPATIBILITY

- - Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result.

HAZCHEM

•3Y

Section 6 - ACCIDENTAL RELEASE MEASURES

MINOR SPILLS

- - Remove all ignition sources.
- Clean up all spills immediately.
- Avoid breathing vapours and contact with skin and eyes.
- Control personal contact with the substance, by using protective equipment.

MAJOR SPILLS

- - Clear area of personnel and move upwind.
- Alert Fire Brigade and tell them location and nature of hazard.
- May be violently or explosively reactive.
- Wear breathing apparatus plus protective gloves.

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

Section 7 - HANDLING AND STORAGE

PROCEDURE FOR HANDLING

- Contains low boiling substance:
Storage in sealed containers may result in pressure buildup causing violent rupture of containers not rated appropriately.
- Check for bulging containers.
- Vent periodically
- Always release caps or seals slowly to ensure slow dissipation of vapours.
- DO NOT allow clothing wet with material to stay in contact with skin.
- Avoid all personal contact, including inhalation.
- Wear protective clothing when risk of overexposure occurs.
- Use in a well-ventilated area.
- Prevent concentration in hollows and sumps.

SUITABLE CONTAINER

- - Packing as supplied by manufacturer.
- Plastic containers may only be used if approved for flammable liquid.
- Check that containers are clearly labelled and free from leaks.

WATTYL ESTAPOL INTERIOR POLYURETHANE GLOSS RANGE

Chemwatch Independent Material Safety Data Sheet

Issue Date: 3-Dec-2012

9317SP(cs)

CHEMWATCH 4796-75

Version No:1.1.1.1

CD 2012/4 Page 4 of 8

Section 7 - HANDLING AND STORAGE

- For low viscosity materials (i) : Drums and jerry cans must be of the non-removable head type. (ii) : Where a can is to be used as an inner package, the can must have a screwed enclosure.
- For materials with a viscosity of at least 2680 cSt. (23 deg. C)
- For manufactured product having a viscosity of at least 250 cSt. (23 deg. C)
- Manufactured product that requires stirring before use and having a viscosity of at least 20 cSt (25 deg. C).

STORAGE INCOMPATIBILITY

- - Avoid reaction with oxidising agents.

STORAGE REQUIREMENTS

- - Store in original containers in approved flammable liquid storage area.
- Store away from incompatible materials in a cool, dry, well-ventilated area.
- DO NOT store in pits, depressions, basements or areas where vapours may be trapped.
- No smoking, naked lights, heat or ignition sources.

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE CONTROLS

The following materials had no OELs on our records

- TDI / pentaerythritol monoricinoleate copolymer:

CAS:52390- 75- 7

ODOUR SAFETY FACTOR (OSF)

OSF=0.042 (mineral turpentine)

- Exposed individuals are NOT reasonably expected to be warned, by smell, that the Exposure Standard is being exceeded.

Odour Safety Factor (OSF) is determined to fall into either Class C, D or E.

The Odour Safety Factor (OSF) is defined as:

OSF= Exposure Standard (TWA) ppm/ Odour Threshold Value (OTV) ppm

Classification into classes follows:

Class	OSF	Description
A	550	Over 90% of exposed individuals are aware by smell that the Exposure Standard (TLV- TWA for example) is being reached, even when distracted by working activities
B	26- 550	As " A" for 50- 90% of persons being distracted
C	1- 26	As " A" for less than 50% of persons being distracted
D	0.18- 1	10- 50% of persons aware of being tested perceive by smell that the Exposure Standard is being reached
E	<0.18	As " D" for less than 10% of persons aware of being tested

MATERIAL DATA

MINERAL TURPENTINE:

- for benzene

Odour Threshold Value: 34 ppm (detection), 97 ppm (recognition)

NOTE: Detector tubes for benzene, measuring in excess of 0.5 ppm, are commercially available. The relative quality of epidemiological data and quantitative health risk assessments related to documented and theoretical leukaemic deaths constitute the basis of the TLV-recommendation.</>

For trimethyl benzene as mixed isomers (of unstated proportions)

Odour Threshold Value: 2.4 ppm (detection)

Use care in interpreting effects as a single isomer or other isomer mix. Trimethylbenzene is an eye, nose and respiratory irritant.

Odour threshold: 0.25 ppm.

The TLV-TWA is protective against ocular and upper respiratory tract irritation and is recommended for bulk handling of gasoline based on calculations of hydrocarbon content of gasoline vapour.

For white spirit:

Low and high odour thresholds of 5.25 and 157.5 mg/m³, respectively, were considered to provide a rather useful index of odour as a warning property.

The TLV-TWA is calculated from data on the toxicities of the major ingredients and is intended to minimise the potential for irritative and narcotic effects, polyneuropathy and kidney damage produced by vapours.</>

for ethyl benzene:

Odour Threshold Value: 0.46-0.60 ppm

continued...

WATTYL ESTAPOL INTERIOR POLYURETHANE GLOSS RANGE

Chemwatch Independent Material Safety Data Sheet

Issue Date: 3-Dec-2012

9317SP(cs)

CHEMWATCH 4796-75

Version No:1.1.1.1

CD 2012/4 Page 5 of 8

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

NOTE: Detector tubes for ethylbenzene, measuring in excess of 30 ppm, are commercially available.

Ethyl benzene produces irritation of the skin and mucous membranes and appears to produce acute and chronic effects on the central nervous system.

for xylenes:

IDLH Level: 900 ppm

Odour Threshold Value: 20 ppm (detection), 40 ppm (recognition)

NOTE: Detector tubes for o-xylene, measuring in excess of 10 ppm, are available commercially. (m-xylene and p-xylene give almost the same response).

CEL TWA: 80 ppm, 480 mg/m3 [Shell]

TDI / PENTAERYTHRITOL MONORICINOLEATE COPOLYMER:

■ for isocyanates:

Some jurisdictions require that health surveillance be conducted on occupationally exposed workers. This should emphasise:

- demography, occupational and medical history and health advice
- completion of a standardised respiratory questionnaire
- physical examination of the respiratory system and skin
- standardised respiratory function tests such as FEV1, FVC and FEV1/FVC.

PERSONAL PROTECTION

RESPIRATOR

•Type A Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

EYE

■ - Safety glasses with side shields.

- Chemical goggles.

- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lens or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59], [AS/NZS 1336 or national equivalent].

HANDS/FEET

■ - Wear chemical protective gloves, e.g. PVC.

- Wear safety footwear or safety gumboots, e.g. Rubber.

NOTE:

- The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact.

- Contaminated leather items, such as shoes, belts and watch-bands should be removed and destroyed.

OTHER

■ - Overalls.

- PVC Apron.

- PVC protective suit may be required if exposure severe.

- Eyewash unit.

ENGINEERING CONTROLS

■ Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.

The basic types of engineering controls are:

Process controls which involve changing the way a job activity or process is done to reduce the risk.

Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE

Colourless clear to hazy flammable liquid with a mild solvent odour; not miscible with water.

PHYSICAL PROPERTIES

Liquid.

Does not mix with water.

Floats on water.

continued...

WATTYL ESTAPOL INTERIOR POLYURETHANE GLOSS RANGE

Chemwatch Independent Material Safety Data Sheet

Issue Date: 3-Dec-2012

9317SP(cs)

CHEMWATCH 4796-75

Version No:1.1.1.1

CD 2012/4 Page 6 of 8

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

State	Liquid	Molecular Weight	Not Applicable
Melting Range (°C)	Not Available	Viscosity	Not Available
Boiling Range (°C)	150- 200	Solubility in water (g/L)	Immiscible
Flash Point (°C)	34 (OC)	pH (1% solution)	Not Applicable
Decomposition Temp (°C)	Not Available	pH (as supplied)	Not Applicable
Autoignition Temp (°C)	250	Vapour Pressure (kPa)	Not Available
Upper Explosive Limit (%)	3.5	Specific Gravity (water=1)	0.90 - 0.94
Lower Explosive Limit (%)	1.0	Relative Vapour Density (air=1)	> 1
Volatile Component (%vol)	50- 60 approx	Evaporation Rate	Not Available

Section 10 - STABILITY AND REACTIVITY

CONDITIONS CONTRIBUTING TO INSTABILITY

- - Presence of incompatible materials.
 - Product is considered stable.
 - Hazardous polymerisation will not occur.
- For incompatible materials - refer to Section 7 - Handling and Storage.*

Section 11 - TOXICOLOGICAL INFORMATION

POTENTIAL HEALTH EFFECTS

ACUTE HEALTH EFFECTS

SWALLOWED

■ Considered an unlikely route of entry in commercial/industrial environments. The liquid may produce gastrointestinal discomfort and may be harmful if swallowed. Ingestion may result in nausea, pain and vomiting. Vomiting entering the lungs by aspiration may cause potentially lethal chemical pneumonitis.

EYE

■ This material can cause eye irritation and damage in some persons.

SKIN

■ Skin contact with the material may damage the health of the individual; systemic effects may result following absorption. This material can cause inflammation of the skin on contact in some persons. The material may accentuate any pre-existing dermatitis condition.

Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.

INHALED

■ Inhalation of aerosols (mists, fumes), generated by the material during the course of normal handling, may be harmful. The material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage.

Inhalation of high concentrations of gas/vapour causes lung irritation with coughing and nausea, central nervous depression with headache and dizziness, slowing of reflexes, fatigue and inco-ordination.

Central nervous system (CNS) depression may include general discomfort, symptoms of giddiness, headache, dizziness, nausea, anaesthetic effects, slowed reaction time, slurred speech and may progress to unconsciousness. Serious poisonings may result in respiratory depression and may be fatal.

The use of a quantity of material in an unventilated or confined space may result in increased exposure and an irritating atmosphere developing. Before starting consider control of exposure by mechanical ventilation.

If exposure to highly concentrated solvent atmosphere is prolonged this may lead to narcosis, unconsciousness, even coma and possible death.

CHRONIC HEALTH EFFECTS

■ Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure.

Asthma-like symptoms may continue for months or even years after exposure to the material ceases. This may be due to a non-allergenic condition known as reactive airways dysfunction syndrome (RADS) which can occur following exposure to high levels of highly irritating compound.

There is limited evidence that, skin contact with this product is more likely to cause a sensitisation reaction in some persons compared to the general population.

There is some evidence from animal testing that exposure to this material may result in toxic effects to the unborn baby.

Sensitisation reactions may appear suddenly after repeated symptom free exposures.

Chronic solvent inhalation exposures may result in nervous system impairment and liver and blood changes. [PATTYS].

continued...

WATTYL ESTAPOL INTERIOR POLYURETHANE GLOSS RANGE

Chemwatch Independent Material Safety Data Sheet

Issue Date: 3-Dec-2012

9317SP(cs)

CHEMWATCH 4796-75

Version No:1.1.1.1

CD 2012/4 Page 7 of 8

Section 11 - TOXICOLOGICAL INFORMATION

TOXICITY AND IRRITATION

■ Not available. Refer to individual constituents.

Section 12 - ECOLOGICAL INFORMATION

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

This material and its container must be disposed of as hazardous waste.

Ecotoxicity

Ingredient	Persistence: Water/Soil	Persistence: Air	Bioaccumulation	Mobility
mineral turpentine	No Data Available	No Data Available	No Data Available	No Data Available
TDI / pentaerythritol monoricinoleate copolymer	No Data Available	No Data Available	No Data Available	No Data Available

Section 13 - DISPOSAL CONSIDERATIONS

■ - Consult manufacturer for recycling options and recycle where possible .

- Consult State Land Waste Management Authority for disposal.
- Incinerate residue at an approved site.
- Recycle containers if possible, or dispose of in an authorised landfill.
- Containers may still present a chemical hazard/ danger when empty.
- Return to supplier for reuse/ recycling if possible.

Otherwise:

- If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill.
- Where possible retain label warnings and MSDS and observe all notices pertaining to the product.

Section 14 - TRANSPORTATION INFORMATION

Labels Required: FLAMMABLE LIQUID

HAZCHEM:

•3Y (ADG7)

ADG7:

Class or Division:	3	Subsidiary Risk:	None
UN No.:	1263	Packing Group:	III
Special Provision:	163 223 *	Limited Quantity:	5 L
Portable Tanks & Bulk Containers - Instruction:	T2	Portable Tanks & Bulk Containers - Special Provision:	TP1 TP29
Packagings & IBCs - Packing Instruction:	P001 IBC03 LP01	Packagings & IBCs - Special Packing Provision:	PP1

Name and Description: PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound) (see 3.2.5 for relevant [AUST.] entries)

Land Transport UNDG:

Class or division:	3	Subsidiary risk:	None
UN No.:	1263	UN packing group:	III
Shipping Name: PAINT or PAINT RELATED MATERIAL (including paint thinning or reducing compound)			

Air Transport IATA:

ICAO/IATA Class:	3	ICAO/IATA Subrisk:	None
UN/ID Number:	1263	Packing Group:	III
Special provisions:	A3		
Cargo Only			
Packing Instructions:	366	Maximum Qty/Pack:	220 L

continued...

WATTYL ESTAPOL INTERIOR POLYURETHANE GLOSS RANGE

Chemwatch Independent Material Safety Data Sheet

Issue Date: 3-Dec-2012

9317SP(cs)

CHEMWATCH 4796-75

Version No:1.1.1.1

CD 2012/4 Page 8 of 8

Section 14 - TRANSPORTATION INFORMATION

Passenger and Cargo Packing Instructions:	355	Passenger and Cargo Maximum Qty/Pack:	60 L
Passenger and Cargo Limited Quantity Packing Instructions:	Y344	Passenger and Cargo Limited Quantity Maximum Qty/Pack:	10 L

Shipping name:PAINT or PAINT RELATED MATERIAL

Maritime Transport IMDG:

IMDG Class:	3	IMDG Subrisk:	None
UN Number:	1263	Packing Group:	III
EMS Number:	F- E, S- E	Special provisions:	163 223 955
Limited Quantities:	5 L		

Shipping name:PAINT or PAINT RELATED MATERIAL

Section 15 - REGULATORY INFORMATION

Indications of Danger:

Xn Harmful

POISONS SCHEDULE None

REGULATIONS

Regulations for ingredients

No data for Wattyl Estapol Interior Polyurethane Gloss Range (CW: 4796-75)

No data for Wattyl Estapol Interior Polyurethane Gloss Range (CAS: , Not avail)

No data for Wattyl Estapol Interior Polyurethane Gloss Range (CAS: , 52390-75-7)

Section 16 - OTHER INFORMATION

■ Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:

www.chemwatch.net/references.

■ The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings.

This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.

Issue Date: 3-Dec-2012

Print Date: 3-Dec-2012

This is the end of the MSDS.