

Manufacturer: Bodytech

Product: Heavy Duty Epoxy

DESCRIPTION:

Bodytech Heavy Duty Epoxy is not only a rust stopping primer, but combines finish and protective coatings all in the one can. Formulated for exterior, or interior use on metal, it can also be used on wood and masonry. The special epoxy resins provide greater adhesion, longer wear and improved chemical resistance. Touch dry – 15 minutes. Full dry – overnight.

DIRECTIONS FOR USE:

1. Remove loose rust with either a wire brush, scraper or abrasive paper and treat remaining rust with rust dissolver. Previously painted surfaces should be lightly sanded. Remove all dirt, grease, oil and wax from surface thoroughly before painting with wax and grease remover.
2. Mask surrounding area to prevent from overspray.
3. Do not spray in conditions of high humidity and temperatures below 10°C.
4. Shake can vigorously for at least 2 minutes after ball bearings begin to rattle. Shake occasionally during spraying.
5. Hold can upright 15 to 30cm from surface, point the spray nozzle at the surface to be painted, press the sprayhead down all the way and spray with smooth overlapping horizontal strokes from side to side. At the end of each stroke release the sprayhead. Spray light coats, allowing each coat to dry for 5 minutes and repeat as many times as necessary to completely cover the surface. If paint sags or runs you are too close or applying too heavily. Dries hard in 24 hours.
6. After use, turn can upside down and spray for 3 seconds to clean nozzle. Clogged sprayheads can be cleaned by removing with a twist and soaking in general purpose thinners.

SAFETY

KEEP OUT OF REACH OF CHILDREN. Avoid contact with skin and eyes and breathing vapour or spray mist. Use only in a well ventilated away from direct heat.

FIRST AID

If sprayed on skin, wipe off, then wash thoroughly with soap and water. If in eyes, hold eyes open and flood with water for at least 15 minutes and see a doctor.

WARNING

Intentional misuse by deliberately concentrating and inhaling contents can be harmful or fatal.

CAUTION

- PRESSURISED DISPENSER.
- PROTECT FROM SUNLIGHT, AND DO NOT EXPOSE TO TEMPERATURES EXCEEDING 50°C.
- DO NOT PEIRCE OR BURN EVEN AFTER USE.
- DO NOT SPRAY ON NAKED FLAME OR ANY INCANDESCENT MATERIAL.
- KEEP AWAY FROM SOURCES OF IGNITION – NO SMOKING.

WASTE

Dispose of container responsibly as directed by your local government.

WARRANTY

Bodytech products are manufactured and tested to specific quality standards. Bodytech guarantee the quality of its products but, being beyond our control, accept no responsibility for the conditions and methods under which they are used. Bodytech will replace any product determined defective but, accept no liability for any injury, loss or damage incurred from use or misuse of our products.

TECHNICAL HELP

Free call: 1800 060 302

Email: TechSupport@khsurfacetech.aust.com

Web site: www.bodytech.com.au

BODYTECH AUSTRALIA

105 South Gippsland

Dandenong, Victoria, Australia, 3175

PH (03) 9792 5927

FAX (03) 9794 5633



LEAD FREE

ROPELLENT: OZONE FREE HYDROCARBONS

MADE IN AUSTRALIA