



# SAFETY DATA SHEET

## SECTION 1 IDENTIFICATION: PRODUCT IDENTIFIER AND CHEMICAL IDENTITY

<b>Product Identifier</b>	<b>FIBREGLASS RESIN</b>
<b>Other Names</b>	Unsaturated polyester resin in styrene/methyl methacrylate solution
<b>Manufacturer's Product Code</b>	FIR
<b>Recommended Use</b>	Manufacture of reinforced and filled plastic composites e.g. fibreglass products

### Details of Supplier/Manufacturer

Company:	Recochem Inc. ABN: 69 010 485 999
Address:	1809 Lytton Road, Lytton, Queensland 4178
Phone:	(07) 3308 5200 Fax: (07) 3308 5201
Website:	www.recochem.com.au


### Emergency Telephone Numbers

Business Hours:	(07) 3308 5200
After Hours:	1300 131 001
Poisons Information:	Australia: 13 11 26 New Zealand: 0800 764 766

## SECTION 2 HAZARDS IDENTIFICATION

<b>Hazardous chemical</b>	<i>according to classification by Safe Work Australia</i>
<b>Dangerous goods</b>	<i>according to the Australian Code for the Transport of Dangerous Goods by Road and Rail</i>

<b>Signal Word</b>	<b>WARNING</b>
--------------------	----------------

GHS Classification	Pictogram	Hazard statement
Flammable Liquids, Category 3	 FLAME	H226 Flammable liquid and vapour

**Product: FIBREGLASS RESIN**

Skin Corrosion/Irritation, Category 2	 EXCLAMATION MARK	H315 Causes skin irritation
Sensitisation - Skin, Category 1		H317 May cause an allergic skin reaction
Eye Damage/Irritation, Category 2A		H319 Causes serious eye irritation
Acute Toxicity – Inhalation, Category 4		H332 Harmful if inhaled

**Precautionary statements:**

<i>GENERAL</i>	
P101	If medical advice is needed, have product container or label at hand
P102	Keep out of reach of children
P103	Read label before use
<i>PREVENTATIVE</i>	
P210	Keep away from heat/sparks/open flames/hot surfaces. - No smoking
P233	Keep container tightly closed
P240	Ground/bond container and receiving equipment
P241	Use explosion-proof electrical/ventilation/lighting equipment
P242	Use only non-sparking tools
P243	Take precautionary measures against static discharge
P261	Avoid breathing mist/vapours/spray
P264	Wash thoroughly after handling
P271	Use only outdoors or in a well-ventilated area
P272	Contaminated work clothing should not be allowed out of the workplace
P280	Wear protective gloves/eye protection/face protection
<i>RESPONSE</i>	
P302 + P352	IF ON SKIN: Wash with plenty of soap and water
P303 + P361 + P353	IF ON SKIN (or hair): Take off contaminated clothing and wash before reuse. Rinse skin with water/shower
P304 + P340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P312	Call a POISON CENTER or doctor/physician if you feel unwell
P332 + P313	If skin irritation occurs: Get medical advice/attention
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention
P337 + P313	If eye irritation persists: Get medical advice/attention
P362	Take off contaminated clothing and wash before reuse
P363	Wash contaminated clothing before reuse
P370 + P378	In case of fire: Use foam/water spray/fog for extinction
<i>STORAGE</i>	
P403 + P235	Store in a well-ventilated place. Keep cool
<i>DISPOSAL</i>	
P501	Dispose of contents/container in accordance with local regulations

---

**SECTION 3 COMPOSITION AND INFORMATION ON INGREDIENTS**

---

**Ingredients Names and Proportions**

Chemical Entity	CAS Number	Proportion (%)
Unsaturated polyester resin (non-hazardous)	-	45 - 75
Styrene	100-42-5	24 - 54
Methyl Methacrylate	80-62-6	1 - 8

---

**SECTION 4 FIRST AID MEASURES**

---

**Description of necessary first aid measures**

Inhalation:	Remove victim from exposure if safe to do so. If rapid recovery does not occur, transport to nearest medical facility for additional treatment. Remove contaminated clothing.
Skin Contact:	If skin contact occurs, remove contaminated clothing, wipe resin off skin. Wash skin thoroughly with soap and water. Wash clothing before reuse.
Eye Contact:	If in eyes, hold eyes open, flood with water for at least 15 minutes. Seek immediate medical assistance.
Ingestion:	If swallowed, do NOT induce vomiting. Give a glass of water. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. Contact a Poison Information centre or a doctor.

**Symptoms caused by exposure**

Inhalation:	May cause irritation to the upper respiratory tract and central nervous system effects (dizziness, drowsiness, euphoria, loss of coordination, headache, nausea and vomiting). In poorly ventilated areas or confined spaces, unconsciousness and asphyxiation may result.
Skin:	May cause irritation and discomfort, redness and swelling. Prolonged contact may cause severe irritation and discomfort. May result in sensitisation and allergic contact dermatitis (itching, drying, redness). Based on data of pure methyl methacrylate, skin contact may be a significant route of exposure with effects similar to those described for inhalation (central nervous system depression)
Eye:	May cause irritation, discomfort and pain. Produces redness, possible swelling of the eye and possible injury to the cornea.
Ingestion:	Styrene and Methyl Methacrylate may cause irritation to the mouth and throat, with abdominal discomfort, nausea and vomiting.

**Medical attention and special treatment**

Treat symptomatically.

---

**SECTION 5 FIRE FIGHTING MEASURES**

---

**Suitable extinguishing equipment**

Use water fog or spray, foam, dry agent.

**Specific hazards arising from the chemical**

Flammable liquid. Polymerisable in a fire situation. Carbon monoxide and/or carbon dioxide may be evolved, along with Styrene, Methyl Methacrylate and acrid smoke. Vapours are heavier than air and can accumulate in low areas. Vapours may travel a considerable distance to a source of ignition and flash back. Heating can cause expansion or decomposition leading to violent rupture of containers.

**Special protective equipment and precautions for fire fighters**

Wear full protective clothing and self-contained breathing apparatus. Hazchem code ●3Y.

---

**SECTION 6 ACCIDENTAL RELEASE MEASURES**

---

**Personal precautions, protective equipment and emergency procedures**

Avoid contact with spilled or released material. Increase ventilation. Shut off leaks, if possible without personal risks. Isolate hazard area and deny entry to unnecessary or unprotected personnel. Remove all sources of ignition in the surrounding area. Take precautionary measure against static discharge. Ensure electrical continuity by bonding and earthing all equipment.

**Environmental precautions**

Use appropriate containment to avoid environmental contamination. Prevent from spreading and entering waterway using dry earth, sand or other non-combustible and inert material.

**Methods and materials for containment and cleaning up**

For small spills (< 1 drum), transfer by mechanical means to a labelled, sealable container for product recovery or safe disposal. Use an appropriate absorbent material and dispose of safely.

For larger spills (> 1 drum), transfer by means such as a vacuum truck to a salvage tank for recovery or disposal. Retain as contaminated waste. Allow any residues to evaporate or use an appropriate absorbent material and dispose of safely.

---

**SECTION 7 HANDLING AND STORAGE**

---

**Precautions for safe handling**

Flammable product. Keep exposure to this product to a minimum. Handle and open containers with care in a well-ventilated area. Ensure that the workplace is ventilated such that the Occupational Exposure limit is not exceeded. Avoid breathing material. Avoid contact with skin, eyes and clothing. Wash thoroughly after handling. Do not eat, drink or smoke in contaminated areas. Electrostatic charges may be generated during transfer. Electrostatic discharge may cause fire. Ensure electrical continuity by earthing all equipment.

**Conditions for safe storage, including any incompatibilities**

Store in a well-ventilated area, away from sunlight, ignition sources and other sources of heat.

---

**SECTION 8 EXPOSURE CONTROLS AND PERSONAL PROTECTION**

---

**Exposure control measures**

From National Occupational Health & Safety Commission (NOHSC) Worksafe Australia -  
Styrene: 213mg/m<sup>3</sup> (50ppm) TWA (8hr), 426mg/m<sup>3</sup> (100ppm) STEL  
Methyl Methacrylate: 208mg/m<sup>3</sup> (50ppm) TWA (8hr), 416mg/m<sup>3</sup> (100ppm) STEL

**Biological monitoring**

No biological limit allocated.

**Engineering controls**

Ensure that adequate ventilation is provided. Maintain air concentrations below recommended exposure standards. Avoid generating and inhaling mists and vapours. Keep containers closed when not in use.

**Individual protection measures**

Eye and face protection:	Eyes should be completely protected with splash resistant goggles with face shield. All surrounding skin should be covered.
Skin protection:	Use solvent resistant gloves (nitrile, neoprene, butyl rubber or Teflon). Use chemical resistant boots and apron. Ensure that all skin areas are completely covered using impermeable gloves, overalls, hair covering and face shield.
Respiratory protection:	If work practices do not maintain airborne level below the exposure standard, use appropriate respiratory protection equipment. When using respirators, select an appropriate combination of mask and filter. Select a filter for organic gases and vapours (boiling point > 65°C). Respirators should comply with AS1716 or an equivalent approved by a state/territory authority.
Thermal hazards:	Not applicable.

---

**SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES**

---

Appearance:	Clear to opaque, viscous liquid
Odour:	Sweet or sharp aromatic
Odour threshold (ppm):	Data not available
pH:	Data not available
Melting point/freezing point (°C):	Data not available
Initial boiling point and boiling range (°C):	100 approx – may polymerise below boiling point
Flash point (°C):	23 - 33 (closed cup)
Evaporation rate (Butyl acetate = 1):	Data not available
Flammability:	Flammable
Upper/lower flammability or explosive limits (%):	1.1 – 12.5
Vapour pressure (mmHg @ 20°C):	35
Vapour density (air = 1 @ 15°C):	> 1
Density (g/ml @ 15°C):	1.1 – 12.5
Solubility (kg/m <sup>3</sup> ):	Insoluble
Partition coefficient: n-octanol/water:	Data not available
Auto-ignition temperature (°C):	490 (Styrene)
Decomposition temperature (°C):	Data not available
Kinematic viscosity (mm <sup>2</sup> /s @ 20°C):	Data not available

---

**SECTION 10 STABILITY AND REACTIVITY**

---

**Reactivity**

Stable under normal conditions of use.

**Chemical stability**

Stable under normal conditions of use.

**Possibility of hazardous reactions**

Stable under normal conditions of use.

**Conditions to avoid**

Keep away from sunlight, heat, sparks, open flames and other ignition sources.

**Incompatible materials**

Avoid contamination with material such as alkylation catalysts (sulphuric acid, phosphoric acid, boron trifluoride, aluminium trichloride), halogen and hydrogen halides, alkali metal-metal graphite compounds and butyl lithium and organic peroxides which catalyse rapid polymerisation of the styrene monomer.

**Hazardous decomposition products**

Burning can produce carbon monoxide, carbon dioxide, styrene, methyl methacrylate and acrid smoke.

**SECTION 11 TOXICOLOGICAL INFORMATION**

Acute toxicity:	Inhalation may cause irritation to the upper respiratory tract and central nervous system effects. May result in the absorption of potentially harmful amounts of material. Swallowing may cause irritation to the mouth and throat
Skin corrosion/irritation:	May cause irritation. Repeated skin contact may cause irritant contact dermatitis
Serious eye damage/irritation:	May cause irritation
Respiratory or skin sensitisation:	May cause skin sensitisation resulting in allergic contact dermatitis (due to methyl methacrylate)
Germ cell mutagenicity:	Not expected to be mutagenic
Carcinogenicity:	Styrene is classified by the international Agency for Research of Cancer (I.A.R.C.) under Group 2B i.e. possibly carcinogenic to humans (sufficient evidence in animals, inadequate data in humans)
Reproductive toxicity:	Not expected to impair reproduction
Specific Target Organ Toxicity (STOT) – single exposure:	Data not available
Specific Target Organ Toxicity (STOT) – repeated exposure:	Data not available.
Aspiration hazard:	Data not available

**SECTION 12 ECOLOGICAL INFORMATION**

**Ecotoxicity**

Acute toxicity:

Fish –	Moderately toxic: LC50 (96hr) 10mg/litre (Fathead minnow)
Aquatic invertebrate –	Moderately toxic: EC50 (48hr) 4.7mg/litre (Daphnia magna)
Algae –	Highly toxic: EC50 (96hr) 0.72mg/litre (Green algae)
Microorganisms –	Data not available

Chronic toxicity:

Fish –	Data not available
Aquatic invertebrate –	Data not available
Algae –	Data not available
Microorganisms –	Data not available

**Persistence and degradability**

Styrene is not expected to persist in the environment.

**Bioaccumulative potential**

Data not available.

**Mobility in soil**

Styrene is expected to bind to soils and sediments and have low mobility.

**Other adverse effects**

Data not available.

**Product: FIBREGLASS RESIN**

---

**SECTION 13 DISPOSAL CONSIDERATIONS**

---

Ensure waste disposal conforms to local waste disposal regulations.

---

**SECTION 14 TRANSPORT INFORMATION**

---

<b>UN number:</b>	1866
<b>Proper shipping name:</b>	Resin solution, flammable
<b>Australian Dangerous Goods class:</b>	3
<b>Australian Dangerous Goods packing group:</b>	III
<b>Hazchem code:</b>	●3Y

---

**SECTION 15 REGULATORY INFORMATION**

---

Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP), Poisons Schedule:	5
Australian Inventory of Chemical Substances (AICS):	Listed
Dangerous Goods Initial Emergency Response Guide (SAA/SNZ HB76):	14

---

**SECTION 16 OTHER INFORMATION**

---

<b>Date of preparation:</b>	16/12/2015
<b>Revision number:</b>	4
<b>Changes in this revision:</b>	Update to GHS SDS standard

---

This SDS summarises product safety information at the date of issue, to the best of our knowledge, as a general guide. Recochem cannot anticipate or control the conditions under which the product is used, so prior to usage each user must assess and control the risks associated with their use of the product. Users should also consult the relevant legislation governing the use and storage of this product. We make no warranties, express or implied, and assume no liability in connection with any use of information contained within this document. If clarification or further information is needed, the user should contact Recochem on (07) 3308 5200.

---